

#8034 SILICONE LUBRICANT

DESCRIPTION: A cost-effective, silicone-based lubricant. Excellent in temperatures -50°F - 450°F (-46°C - 232°C). Contains 5% silicone. Odorless, colorless and won't stain.

DIRECTIONS: Spray uniformly 6-10" away from surface. Use firm pressure on sprayhead and spray away from you. For hard to reach areas, use the extension tube. For best results use at room temperature. **DO NOT USE ON ELECTRICAL EQUIPMENT OR MACHINERY WHILE IN OPERATION.**

DANGER! Never use or store near sparks, heat, open flame or sources of ignition. Do not puncture, incinerate or store container above 120°F (49°C). May cause flash fire. **VAPOR HARMFUL.** Avoid continuous breathing of vapors and mist. Use with adequate ventilation. If you experience eye watering, headaches, nausea or dizziness, increase fresh airflow and/or wear NIOSH approved respiratory protection. **AVOID CONTACT WITH SKIN AND EYES.** **FIRST AID:** If swallowed, do not induce vomiting and seek medical attention immediately. If eye contact occurs, flush eyes with plenty of water for 15 minutes. For skin contact, wash thoroughly with soap and water. In either case, if irritation persists, see physician immediately. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DESCRIPTION : Un lubrifiant à base de silicone rentable. Excellent avec des températures de -46° C à - 232° C (-50°F à - 450°F). Contient 5% de silicone. Inodore, incolore et ne tache pas.

INSTRUCTIONS : Pulvériser uniformément à 15-25 cm de la surface. Utilisez une pression ferme sur sprayhead et vaporiser loin de nous. Pour les endroits difficiles à atteindre, utilisez le tube prolongateur. Pour de meilleurs résultats, utilisez à température ambiante. **NE PAS UTILISER SUR DES ÉQUIPEMENTS ÉLECTRIQUES OU DES MACHINES EN FONCTIONNEMENT.**

DANGER ! Tenir loin des sources de chaleur, des étincelles et des flammes nues. Ne pas brûler, incinérer ou entreposer à des températures au-dessus de 120°F (49°C). Peut causer un embrasement éclair. **VAPEURS NOCIVES.** Éviter de respirer en continu les vapeurs et les fines gouttelettes. Utiliser avec une ventilation adéquate. Si les yeux pleurent, ou si l'on ressent des maux de tête ou des étourdissements, augmenter la quantité d'air frais et/ou porter une protection respiratoire approuvée par NIOSH. **NOCIF OU FATAL SI INGÈRE.** **ÉVITER LE CONTACT AVEC LA PEAU ET LES YEUX.** **PREMIERS SECOURS :** En cas d'ingestion, ne pas faire vomir. Appeler immédiatement un médecin. En cas de contact avec les yeux, rincer les yeux avec beaucoup d'eau pendant 15 minutes et consulter un médecin. En cas de contact avec la peau, laver au savon et à l'eau. Dans les deux cas, si l'irritation persiste, voyez un médecin immédiatement. **AVIS:** Selon les rapports, une exposition professionnelle excessive et répétée aux solvants a été associée à des lésions permanentes au cerveau et au système nerveux. Une mauvaise utilisation intentionnelle en concentrant délibérément et en inhalant les vapeurs peut être nocif, voire mortel.

DESCRIPCIÓN: Un lubricante a base de silicona rentable. Excelente a temperaturas de -50°F - 450°F (-46°C - 232°C). Contiene 5% de silicona para el uso industrial. Inodoro, incoloro, y no se mancha.

INSTRUCCIONES: Rocíar uniformemente, a una distancia 6-10" de la superficie. Utilice una presión firme sobre la cabeza de rociado y rocíe lejos de usted. Para áreas de difícil acceso, use el tubo de extensión. Para obtener los mejores resultados, utilizar a temperatura ambiente. **NO UTILIZAR SOBRE EQUIPOS ELÉCTRICOS O MAQUINARIA MIENTRAS ESTÉN EN FUNCIONAMIENTO.**

¡PELIGRO! Nunca utilice ni guarde el producto cerca de chispas, fuentes de calor, llamas expuestas ni fuentes de ignición. No perforo, incinere ni guarde el contenedor a temperaturas superiores a los 120°F (49°C). Puede causar un incendio repentino. **VAPOR DANINO.** Evite la inhalación continua de los vapores y el rocío. Use con ventilación adecuada. Si experimenta irritación ocular, dolor de cabeza, náuseas o mareos, aumente el flujo de aire fresco y/o utilice protección respiratoria aprobada por NIOSH. **LOS CONTENIDOS SON DÁÑINOS O MORTALES SI SE TRAGAN. EVITE EL CONTACTO CON LA PIEL Y LOS OJOS.** **PRIMEROS AUXILIOS:** Si se traga, no debe provocar el vómito. Busque atención médica inmediata. En caso de que entre en contacto con los ojos, enjuáguelos inmediatamente por 15 minutos. Si entra en contacto con la piel, lávela minuciosamente con agua y jabón. En cualquiera de estos casos, si la irritación persiste, póngase en contacto con un médico inmediatamente. **AVISO:** Existen informes que han asociado la sobreexposición prolongada a disolventes con daños cerebrales permanentes y daños al sistema nervioso. El uso indebido por concentración e inhalación deliberada del contenido puede ser nocivo o fatal.

HAZARDOUS CONTENTS: Aliphatic Petroleum Distillates 64742-89-8, Hydrocarbon Propellant 68476-86-8, Dimethylsiloxane 63148-62-9, Aliphatic Hydrocarbon 64742-47-8.
VOC Category: Silicone-based Multipurpose Lubricant | **VOC 60%**



DANGER! Extremely flammable aerosol. Pressurized container; may burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long-lasting effects.

DANGER ! Aérosol extrêmement inflammable. Recipient pressurisé; peut éclater si chauffé. Peut être mortel en cas d'ingestion et de pénétration dans les voies respiratoires. Provoque l'irritation de la peau. Peut causer de la somnolence et des vertiges. Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

¡PELIGRO! Aerosol sumamente inflamable. Recipiente a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y penetración en las vías respiratorias. Causa irritación de la piel. Puede causar tóxico para la vida acuática con efectos duraderos, somnolencia y mareos.

KEEP AWAY FROM CHILDREN



AERVOE LLC
A Quintessential Group Company
Gardnerville, NV 89410 | 800-227-0196



SHAKE WELL BEFORE USE

AERVOE

ToolMates

CROWN
M.R.

SILICONE LUBRICANT 8034

Lubrifiant Silicone
Lubricante de Silicona

• Lubricates • Prevents Freezing

The Professional's Choice

DANGER ! EXTRÊMEMENT INFLAMMABLE ! CONTENU SOUS PRESSION. VAPEURS NOCIVES. NOCIF OU FATAL EN CAS D'INGESTION. (Lire les précautions au verso)

DANGER! EXTREMELY FLAMMABLE! CONTENTS UNDER PRESSURE. VAPORS HARMFUL. HARMFUL OR FATAL IF SWALLOWED. (Read cautions on back panel)

¡PELIGRO! ¡EXTREMADAMENTE INFLAMABLE! CONTENIDO BAJO PRESION. VAPORES PERJUDICIALES. PERJUDICIAL O FATAL SI TRAGADO. (Lea cuidados en atrás panel)

Net wt. 10.5 oz. (298 g)

CC


108034; AD 4/28/25

SAFETY DATA SHEET

Section I: Identification

Product identifier: Crown 8034 Silicone Lubricant - Aerosol
Relevant identified uses of the substance: General Purpose Lubricant
Uses advised against: Avoid applying directly onto food products; incidental contact only.
CAS No: Not Applicable (mixture) **EC No:** Not Applicable (mixture)
Index No: Not Applicable (mixture)
Manufacturer/Supplier: Aervoe LLC
 1100 Mark Circle Gardnerville, Nevada 89410
Telephone number: 1-775-782-0100 **e-mail:** mailbox@aervoe.com
For Product Information: 1-800-227-0196
Emergency telephone number: 1-800-424-9300 (Chemtrec-24h)

Section II: Hazards

Classifications Physical Hazards: Flammable Aerosol - Category 1
Environmental Hazards: Aquatic Tox. 2 **Health Hazards:** Asp Tox. 1 Skin Irrit. 2 STOT SE 3.
Labeling Signal Word: Danger
Hazard Statements: Extremely flammable aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long-lasting effects.
Precautionary Statements: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. If on skin or hair, remove/takeoff immediately all contaminated clothing. Rinse skin with water/shower. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulation.
Symbols/Pictograms: 

SECTION III: COMPOSITION/INFORMATION ON INGREDIENTS

Name/Synonym	CAS/EC#	%
Aliphatic Hydrocarbon / Petroleum Distillates	64742-47-8 / 265-149-8	30-60%
Aliphatic Petroleum Distillates/ Solvent Naphtha	64742-89-8 / 265-192-2	15-40%
Hydrocarbon Propellant / LPG	68476-86-8 / 270-705-8	10-30%
Dimethylsiloxane	63148-62-9 / 687-578-3	1-5%

Section IV: First Aid Measures

Inhalation First Aid: Remove victim to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention immediately.

Skin Contact First Aid: Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention if acute symptoms develop. Wash clothing before reuse.

Eye Contact First Aid: If contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention immediately.

Ingestion First Aid: If swallowed, wash out mouth with water provided the person is conscious. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Most Important Symptoms/Effects: Exposure may cause slight irritation to the skin, eyes, and respiratory tract. Excessive exposure may cause central nervous system effects.

General Advice: If symptoms persist, always call a doctor.

Section V: Fire Fighting Measures

Suitable extinguishing media: Carbon dioxide, dry chemical, water spray.

Unsuitable extinguishing media: None known

Hazards arising from the substance/mixture: None known

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Fire & Explosion Hazards: Closed Containers may rupture due to the buildup of pressure from extreme temperatures.

Precautions for fire-fighters: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. In the event of a fire, wear full protective clothing and NIOSH- approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

Section VI: Accidental Release Measures

PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
 - 2) Maintain adequate ventilation.
- SPILL CLEAN-UP PROCEDURES:**
- 1) Evacuate unprotected personnel from the area.
 - 2) Remove sources of ignition if safe to do so.
 - 3) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
 - 4) Contain spill to prevent material from entering sewage or ground water systems.
 - 5) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

Section VII: Storage

Handling: Combustible Aerosol, use in a well ventilated area. Do not use near sources of ignition. Do not to eat, drink and smoke while working with this material. Wash hands after use.

Conditions for safe storage, including any incompatibilities: Store out of direct sunlight. Storage Temperature: 32° to 120°F (0° to 49°C). No known incompatibilities.

Section VIII: Exposure Controls / Personal Protection

Appropriate engineering controls: Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Keep away from sources of ignition. Take precautionary measures against static discharge.

Personal Protection: Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

Skin protection: Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection: Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Ingredient	Exposure Limit	Type
Aliphatic Hydrocarbon	N/AV	N/AV
Hydrocarbon Propellant	N/AV	N/AV

Section IX: Physical and Chemical Properties

Appearance: Clear **Odor:** Hydrocarbon odor
Odor Threshold: N/AV **pH:** Not Applicable (Solvent Base)
Melting Point: N/AV **Freezing Point:** N/AV **Initial Boiling Point:** N/AV
Boiling Point Range: N/AV **Flash Point:** 0° F (-18° C)
Evaporation Rate: Faster than n-Butyl Acetate **Flammability Solid/Gas:** Flammable gas **LEL:** 1.1% **UEL:** 9.5% **Vapor Pressure:** N/AV
Vapor Density: Heavier Than Air **Relative Density:** N/AV
Solubility: Negligible **Partition Coefficient:** N/AV
n-octanol/ water: N/AV **Auto-ignition Temperature:** N/AV
Decomposition Temperature: N/AV **Viscosity:** N/AV
Explosive Properties: N/AV **Oxidizing Properties:** N/AV

Section X: Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions **Chemical stability:** Stable under normal conditions. **Conditions to avoid:** Heat and ignition sources

Incompatible materials: Strong Oxidizing Agents **Hazardous decomposition products:** Will not occur

Section XI: Toxicological Information

Reports have associated repeated/prolonged overexposure to solvents with permanent brain/nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data: Asp. Tox 1 **Eye irritation data:** N/AV

Skin irritation/sensitization/absorption data: Skin Irrit 2

Reproductive toxicity data: N/AV **Mutagenicity data:** N/AV

Symptoms associated with physical contact: N/AV

Acute/chronic effects from short/long term exposure: Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.

Known reportable carcinogens via the following agencies:

NTP: N/AV **IARC:** N/AV **OSHA:** N/AV

Section XII: Ecological

Please visit website for full SDS with additional information.

Section XIII: Disposal Considerations

Please visit website for full SDS with additional information.

UN #	Shipping Name	Hazard Class	Packing Group
US DOT UN1950	Aerosols	2.1	N/AP
IMDG UN1950	Aerosols	2.1	N/AP
IATA UN1950	Aerosols, Flammable	2.1	N/AP

Section XV: Regulatory Information

Please visit website for full SDS with additional information.

Section XVI: Other Information

Date of Preparation/Revision: 4/9/25 **Supersedes:** (2/21/25)

5.8268"

00

No Print Area