

RUST PROOF ANY-WAY SPRAY PAINT

DESCRIPTION: A high quality enamel coating that is designed to adhere well and resist rust on a variety of surfaces. The Spray-Any-Way valve allows it to be sprayed in any direction. Heat resistant to 300°F (149°C).

DIRECTIONS: See Product Data Sheet for complete instructions. A primer is recommended over bare metal. Do not apply below 40°F (4°C) or in rain or high humidity. For best results use at temperatures between 60°F-80°F (16°C-27°C). Shake can for 1 minute after agitator ball is heard and during use. Hold can 6-8" from surface. Apply in multiple thin coats to avoid runs or drips. Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD, or log onto www.epa.gov/lead.

HAZARDOUS CONTENTS: 311 contains Acetone 67-64-1, n-Butyl Acetate 123-86-4, Hydrocarbon Propellant 68476-86-8; 310 contains Aliphatic Petroleum Distillates 64742-89-8, Hydrocarbon Propellant 68476-86-8; all other products contain Acetone 67-64-1, Hydrocarbon Propellant 68476-86-8, Aliphatic Petroleum Distillates 64742-89-8.

DANGER! Extremely flammable aerosol. Pressurized container; may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

KEEP AWAY FROM CHILDREN

DESCRIPTION: Un revêtement en laque de haute qualité conçue pour une bonne adhérence et pour résister à la rouille sur une variété de surfaces. La valve du pulvérisateur Any-Way permet de pulvériser dans n'importe quelle direction. Résistant à la chaleur à 149 °C (300°F).

INSTRUCTIONS: Consultez la fiche technique du produit pour obtenir des instructions complètes. Une amorce recommandée sur le métal nu. Ne pas appliquer à une température inférieure à 40 °F (4 °C) ou sous la pluie ou avec une humidité élevée. Pour de meilleurs résultats, pulvériser à des températures comprises entre 16 °C et 27 °C (60 °F-80 °F). Agiter la bouteille pendant 1 minute après que la boule de l'agitateur soit entendue et pendant l'utilisation. Tenez-vous à 15-20 cm de la surface. Appliquer en plusieurs couches minces pour éviter les coulures ou les gouttes. Avertissement: Si vous enlevez ou grattez le sable ou la vieille peinture, vous pouvez relâcher la poussière de plomb. LE PLOMB EST TOXIQUE. Contacter la Hotline d'information Nationale sur le Plomb ou connectez-vous au www.epa.gov/lead.

DANGER! Tenir loin des sources de chaleur, des étincelles et des flammes nues. Ne pas percer ou incinérer le contenant même lorsqu'il est vide. Ne pas exposer à la chaleur ni entreposer à des températures supérieures à 149°C (300°F). À L'USAGER SEULEMENT AVEC UNE VENTILATION ADEQUATE. PEUT ÊTRE NOCIF SI ABSORBÉ PAR LA PEAU. Peut affecter le cerveau ou le système nerveux provoquant des étourdissements, des maux de tête ou des nausées. Peut causer une irritation de la peau, du nez et de la gorge. Évitez le contact avec les yeux, la peau et les vêtements. Si vous ressentez un larmoiement, des maux de tête, des nausées ou des vertiges, augmentez la circulation d'air frais et / ou portez une protection respiratoire approuvée par le NIOSH. Laver la peau en profondeur avant l'utilisation. **PREMIERS SOINS:** En cas d'ingestion, ne pas faire vomir. Appeler immédiatement un médecin et / ou contacter immédiatement un centre antipoison. En cas de contact avec les yeux, rincer les yeux avec beaucoup d'eau pendant 15 minutes et consulter un médecin. En cas de contact avec la peau, laver au savon et à l'eau. Si vous avez des difficultés à respirer, arrêtez d'utiliser le produit et quittez la zone pour obtenir de l'air frais. En cas de difficultés respiratoires, consulter un médecin. **AVIS:** Selon les rapports, une exposition professionnelle excessive et répétée aux solvants a été associée à des lésions permanentes au cerveau et au système nerveux. UNE MAUVAISE UTILISATION INTENTIONNELLE EN CONCENTRANT DELIBEREMENT ET EN INHALANT LES VAPEURS PEUT ETRE NOCIF, VOIRE MORTEL.

DESCRIPTION: Un revêtement de esmalte de alta calidad que esta diseñado para adherirse bien y resistir la oxidación sobre una variedad de superficies. La válvula del Aerosol-Any-Way le permite ser rociado en cualquier dirección. Resistente al calor hasta 300°F (149°C).

INSTRUCCIONES: Consulte la Hoja de datos del producto para ver las instrucciones completas. Se recomienda sobre metal desnudo. No aplicar en temperaturas por debajo de 40°F (4°C) o en la lluvia o humedad alta. Para obtener mejores resultados, utilice a temperaturas entre 60°F-80°F (16°C-27°C). Agite la lata durante un minuto después de escuchar el movimiento de la bola del agitador, y durante el uso. Coloque la lata a una distancia 6-8" de la superficie. Aplique en múltiples capas delgadas para evitar que se comidos o gotees. ¡Advertencia! Si rasca, tira o elimina pintura antigua, puede liberar polvo de plomo. EL PLOMO ES TOXICO. Póngase en contacto con la Línea de información nacional sobre plomo en el 1-800-424-LEAD, o visite www.epa.gov/lead.

PELIGRO! Nunca utilice ni guarde el producto cerca de chispas, fuentes de calor, llamas o estacas ni fuentes de ignición. No perforo ni incinere el contenedor, aunque este vacío. No exponga al calor ni almacene a temperaturas superiores a 120°F (49°C). USAR SOLO CON LA VENTILACION ADECUADA. PUEDE RESULTAR PELIGROSO SI SE ABSORBE A TRAVES DE LA PIEL. Puede afectar al cerebro o al sistema nervioso causando mareos, dolor de cabeza o náuseas. Puede causar irritación en los ojos, la piel, la nariz y la garganta. Evite el contacto con la piel y la ropa. Si experimenta lagrimeo, dolor de cabeza, náuseas o mareos, aumente el flujo de aire fresco y/o utilice protección respiratoria aprobada por NIOSH. **PRIMEROS AUXILIOS:** En caso de ingestión, no provoque el vómito, busque atención médica y/o póngase en contacto con un centro de toxicología inmediatamente. En caso de contacto con los ojos, enjuáguelos inmediatamente durante 15 minutos y póngase en contacto con los servicios médicos. Si entra en contacto con la piel, lávela minuciosamente con agua y jabón. Si experimenta alguna dificultad para respirar, deje de usar el producto y abandone la zona para respirar aire fresco. Si dicha dificultad persiste, póngase en contacto con los servicios médicos. **AVISO:** Existen informes que han asociado la sobreexposición prolongada a disolventes con daños cerebrales permanentes y daños al sistema nervioso. EL USO INDEBIDO POR CONCENTRACION DEL CONTENIDO DEL CONTENIDO PUEDE SER NOCIVO O FATAL.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et les Problèmes de Reproduction - www.P65Warnings.ca.gov.

ADVERTENCIA: Cáncer y Daños Reproductivos - www.P65Warnings.ca.gov.



KEEP AWAY FROM CHILDREN



AERVOE INDUSTRIES INC.
Gardnerville, NV 89410 • 800-227-0196

Peel Here



RUST PROOF ANY-WAY SPRAY PAINT

Peinture Antirouille en Aérosol
Pintura a Prueba de Herrumbre

Multisurface Paint

Metal • Wood • Plastic

Spray Any Direction

Industrial Grade Performance



DANGER! EXTREMELY FLAMMABLE! CONTENTS UNDER PRESSURE. VAPORS HARMFUL, HARMFUL OR FATAL IF SWALLOWED.
(Read cautions on back panel)

DANGER! EXTRÊMEMENT INFLAMMABLE! CONTENU SOUS PRESSION. VAPEURS NOCIVES, NOCIF OU FATAL EN CAS D'INGESTION.
(Lire les précautions au verso)

PELIGRO! EXTREMADAMENTE INFLAMABLE! CONTENIDO BAJO PRESSION. VAPORES PERJUDICIALES, PERJUDICIAL O FATAL SI TRAGADO.
(Lea cuidados en atrás panel)

Net Wt. 12 oz. (340 g) / Silver 11 oz. (312 g)

SHAKE WELL BEFORE USE

10301; AD 1/11/24

SAFETY DATA SHEET

Section I: Identification

Product identifier: Aervoe Rust Proof Any-Way Spray Paint - Aerosol
157 J.D. Green 167 Cat. Yellow - Old 168 Cat. Yellow - New 178 School Bus
Yellow 300 Safety Purple 301 Safety Red 302 Safety Yellow 303 Safety Blue 304
Safety Green 305 Safety Orange 306 Safety Black 307 Safety White 308 Brite
Red 309 Aluminum 310 Silver 311 Gold 312 Flat Black 313 Flat White 314 Brown
317 Tan 318 Light Blue 319 Royal Blue 320 Forest Green 333 Dk. Gray (ANSI-33)
342 Semi-Flat Black 344 Satin Black 348 Meter Green 349 Meter Gray(ANSI-49)
361 Lt. Gray (ANSI-61)

Relevant identified uses of the substance: Coating

Uses advised against: Poorly ventilated areas.

CAS No: Not Applicable (mixture) **EC No:** Not Applicable (mixture)

Index No: Not Applicable (mixture)

Manufacturer/Supplier: Aervoe Industries, Inc. 1100 Mark Circle Gardnerville,
Nevada 89410

Telephone number: 1-775-782-0100 **e-mail:** mailbox@aervoe.com

For Product Information: 1-800-227-0196

Emergency telephone number: 1-800-424-9300 (Chemtrec-24h)

Section II: Hazards

Classifications Physical Hazards: Flammable Aerosol - Category 1 Liquefied
Gas **Environmental Hazards:** Aquatic Tox. 2 **Health Hazards:** STOT SE 3 Eye
Irrit. 2 Skin Irr. 2 Asp. Tox. 1

Labeling Signal Word: Danger

Hazard Statements: Extremely flammable aerosol. Pressurized container; may
burst if heated. Causes skin irritation. Causes serious eye irritation. May cause
drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to
aquatic life with long lasting effects.

Precautionary Statements: If medical advice is needed, have product container
or label at hand. Keep out of reach of children. Read label before use. Keep away
from heat/sparks/open flames/hot surfaces - no smoking. Do not spray on an
open flame or other ignition source. Pressurized container. Do not pierce or
burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not
get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Wear
protective gloves/eye protection/face protection. If on skin or hair,
remove/takeoff immediately all contaminated clothing. Rinse skin with
water/shower. Protect from sunlight. Do not expose to temperatures exceeding
50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulation.

Symbols/Pictograms:



Section III: Composition / Information on Ingredients

Name/Synonym	CAS/EC#	%
Acetone / Propanone	67-64-1 / 200-662-2	15-40%
Hydrocarbon Propellant / LPG	68476-86-8 / 270-705-8	15-40%
Aliphatic Petroleum Distillates / Solvent Naphtha	64742-89-8 / 265-192-2	10-30%
310 contains:		
Aliphatic Petroleum Distillates / Solvent Naphtha	64742-89-8 / 265-192-2	30-60%
Hydrocarbon Propellant / LPG	68476-86-8 / 270-705-8	30-60%
311 contains:		
Acetone / Propanone	67-64-1 / 200-662-2	30-60%
n-Butyl Acetate / n-Butyl Ester	123-86-4 / 204-658-1	10-30%
Hydrocarbon Propellant / LPG	68476-86-8 / 270-705-8	15-40%

Section IV: First Aid Measures

Inhalation First Aid: Remove victim to fresh air and provide oxygen if breathing
is difficult. If not breathing, give artificial respiration, preferably mouth to mouth.
Get medical attention immediately.

Skin Contact First Aid: Wash with soap and water. Remove contaminated
clothing and shoes. Get medical attention immediately if acute symptoms
develop. Wash clothing before reuse.

Eye Contact First Aid: If contact with eyes, immediately flush eyes with plenty of
water for at least 15 minutes, while holding eyelids open. Get medical attention
immediately.

Ingestion First Aid: If swallowed, wash out mouth with water provided the
person is conscious. Do not induce vomiting. Never give anything by mouth to an
unconscious person. Get medical attention immediately.

Most Important Symptoms/Effects: Exposure may cause slight irritation to the
skin, eyes, and respiratory tract. Excessive exposure may cause central nervous
system effects. **General Advice:** If symptoms persist, always call a doctor.

Section V: Fire Fighting Measures

Suitable extinguishing media: Carbon dioxide, dry chemical, water spray.

Unsuitable extinguishing media: None known

Hazards arising from the substance/mixture: None known

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Fire & Explosion Hazards: Closed Containers may rupture due to the buildup of
pressure from extreme temperatures.

Precautions for fire-fighters: Use water spray to cool containers exposed to
heat or fire to prevent pressure build up. In the event of a fire, wear full protective
clothing and NIOSH- approved self-contained breathing apparatus with full face
piece operated in the pressure demand or other positive pressure mode.

Section VI: Accidental Release Measures

PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

SPILL CLEAN-UP PROCEDURES:

- 1) Evacuate unprotected personnel from the area.
- 2) Remove sources of ignition if safe to do so.
- 3) Pickup spilled materials using non-sparking tools and place in an appropriate
container for disposal.
- 4) Contain spill to prevent material from entering sewage or ground water
systems.
- 5) Always dispose of waste materials in accordance with all EU, National and
Local Regulations.

Section VII: Storage

Handling: Flammable Aerosol, use in a well ventilated area. Do not use near
sources of ignition. Do not to eat, drink and smoke while working with this
material. Wash hands after use. **Conditions for safe storage, including any
incompatibilities:** Store out of direct sunlight. **Storage Temperature:** 32° to
120°F (0° to 49°C). No known incompatibilities.

Section VIII: Exposure Controls / Personal Protection

Appropriate engineering controls: Ensure adequate ventilation. A system of
local and/or general exhaust is recommended to keep employee exposures
below the Airborne Exposure Limits. Keep away from sources of ignition. Take
precautionary measures against static discharge. **Personal Protection:** Eye &
face protection devices such as safety glasses, safety goggles or face shield are
recommended.

Skin protection: Wear the appropriate protective clothing, including boots,
gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection: Use only in an adequately ventilated area. For
unknown vapor concentrations use a positive-pressure, pressure demand,
self-contained breathing apparatus (SCBA).

Ingredient	Exposure Limit	Type
Acetone	250 ppm	ACGIH TLV (TWA)
	500 ppm	ACGIH TLV (STEL)
	1000 ppm	OSHA PEL (TWA)
n-Butyl Acetate	50 ppm	ACGIH TLV (TWA)
	150 ppm	ACGIH TLV (STEL)
	150 ppm	OSHA PEL (TWA)

Section IX: Physical and Chemical Properties

Appearance: Color varies by product **Odor:** Ketone odor **Odor Threshold:** N/AV

pH: Not Applicable (solvent Base) **Melting Point:** N/AV **Freezing Point:** N/AV

Initial Boiling Point: N/AV **Boiling Point Range:** N/AV **Flash Point:** <0° F (-18°

C) **Evaporation Rate:** Faster than n-Butyl Acetate **Flammability Solid/Gas:**

Flammable gas LEL: 0.7% UEL:12.8% **Vapor Pressure:** N/AV **Vapor Density:**

Heavier Than Air **Relative Density:** N/AV **Solubility:** Negligible **Partition**

Coefficient: N/AV n-octanol/ water: N/AV **Auto-ignition Temperature:** N/AV

Decomposition Temperature: N/AV **Viscosity:** N/AV **Explosive Properties:** N/AV

Oxidizing Properties: N/AV

Section X: Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur
under normal conditions **Chemical stability:** Stable under normal conditions.

Conditions to avoid: Heat and ignition sources **Incompatible materials:**

Strong Oxidizing Agents **Hazardous decomposition products:** Will not occur

Section XI: Toxicological Information

Reports have associated repeated/prolonged overexposure to solvents with
permanent brain/nervous system damage. Repeated overexposure can also
damage kidneys, lungs, liver, heart and blood. **Routes of exposure:** Eyes, skin,

ingestion, and/or inhalation **Acute toxicological data:** (Acetone) LD50: 5800
mg/kg (Rat-Oral) (Acetone) LC50: 21000 ppm/8 hr (Rat-Inhale) **Eye irritation data:**

Eye Irrit. 2 **Skin irritation/sensitization/absorption data:** Skin Irrit. 2

Reproductive toxicity data: N/AV **Mutagenicity data:** N/AV

Symptoms associated with physical contact: N/AV **Acute/chronic effects from**

short/long term exposure: Irritating to skin. Prolonged/repeated contact may
cause defatting of the skin which can lead to dermatitis. Not expected to be a skin
sensitizer. **Known reportable carcinogens via the following agencies:** NTP: N/AV

IARC: N/AV **OSHA:** TLV-A4

Section XII: Ecological

Please visit website for full SDS with additional information.

Section XIII: Disposal Considerations

Please visit website for full SDS with additional information.

Section XIV: Transportation

UN #	Shipping Name	Hazard Class	Packing Group
US DOT UN1950	Aerosols	2.1	N/AP
IMDG UN1950	Aerosols	2.1	N/AP
IATA UN1950	Aerosols, Flammable	2.1	N/AP

Section XV: Regulatory Information

Please visit website for full SDS with additional information.

Section XVI: Other Information

Date of Preparation/Revision: 1/11/24 **Supersedes:** (8/25/23).

5.8268"

80

No Print Area