

AERVOE INDUSTRIES

**ToolMates**

# UNDERCOATING AND SOUND INSULATOR 595

- Rubberized and Flexible
- Excellent Corrosion Protection
- Quick Drying

**The Professional's Choice**

**DANGER**  
EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE • VAPORS HARMFUL  
HARMFUL OR FATAL IF SWALLOWED  
(Read caution details on back panel before using)

**Net wt. 15 oz. (425 g)**

## AERVOE #595 UNDERCOATING AND SOUND INSULATOR

**DESCRIPTION:** A quick drying black rubberized film that is exceptionally resistant to abrasion. Seals out dust, water, road chemicals, fumes, heat, and cold. Expanded cell structure deadens sound.

**APPLICATION:** Protects car underbody, seals trunk, fender, and body seams. Excellent corrosion proofer for repairs, rust holes, weld joints, and hidden areas. Tough, yet flexible even under cold conditions; will not crack or peel.

**DIRECTIONS:** Shake well before use. For best results, hold can 10 to 12 inches from surface and apply in a uniform coat. Material is delivered in a rapid stream, so keep the can moving while nozzle is depressed. Use at temperatures from 65° to 90°F (18° to 32°C). If undercoating is to be top coated, use a good quality flexible enamel. Test paint-cured panel (24 hours) to ensure paint compatibility before use.

**DANGER!** Never use or store near any sparks, heat, open flame, or sources of ignition. Do not puncture or incinerate container even when empty. Do Not store at temperatures above 120°F (49°C). **USE ONLY WITH ADEQUATE VENTILATION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN.** If you experience eye watering, headaches, nausea, or dizziness, increase fresh airflow and/or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent). May affect the brain or nervous system causing dizziness, headache, or nausea. Can cause eye, skin, nose, and throat irritation. **FIRST AID:** If swallowed, do not induce vomiting, seek medical attention immediately and/or contact a poison control center immediately. In case of eye contact, flush immediately for 15 minutes and seek medical attention. For skin contact, wash thoroughly with soap and water. If any difficulty in breathing is experienced, stop using product and leave the area to obtain fresh air. If breathing difficulty continues then seek medical attention. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**WARNING:** Cancer and Reproductive Harm - [www.Prop65Warnings.ca.gov](http://www.Prop65Warnings.ca.gov).

**HAZARDOUS CONTENTS:** n-Butyl Acetate 123-86-4, Aliphatic Petroleum Distillates 64742-89-8, Aliphatic Hydrocarbon 64742-47-8, Hydrocarbon Propellant 68476-86-8.

SHAKE WELL BEFORE USE



**DANGER!** Extremely flammable gas. Extremely flammable aerosol. Pressurized container; may burst if heated. Extremely flammable liquid and vapor. Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.



**KEEP AWAY FROM CHILDREN**  
For Safety Data Sheets go to [www.aervoe.com](http://www.aervoe.com).  
**AERVOE INDUSTRIES INC.**  
Gardnerville, NV 89410 • 800-227-0196



18595: SW CS: 5/21/18  
CIPD