

AERVOE INDUSTRIES

ToolMates®

CROWN® M.R.

# RED INSULATING VARNISH 6084

- Dielectric Strength 4000V/mil
- Thermal Rated Class F
- Flexible Film

FOR INDUSTRIAL USE

The Professional's Choice

**DANGER**  
 EXTREMELY FLAMMABLE  
 CONTENTS UNDER PRESSURE • VAPORS HARMFUL  
 HARMFUL OR FATAL IF SWALLOWED  
 (Read caution details on back panel before using)

Net wt. 13 oz. (369 g)

## #6084 RED INSULATING VARNISH

**DESCRIPTION:** This product protects with outstanding adhesion through a Class F epoxy ester. It dries to a flexible, tough, oil-proof film that protects electrical equipment. This film is highly resistant to acids, alkalies, moisture and heat. For use in manufacturing facilities.

**APPLICATIONS:** Use on armature and stator windings, high voltage circuits, commutator ends, coils, frayed insulation, or to restore dielectric properties. This insulating varnish is rated at 4000 volts per mil cured.

**DIRECTIONS:** Shake well for 30 seconds before using. Hold can 12 to 14 inches from object to be sprayed. The darkness of the color indicates the thickness of the coating. Dries tack-free in 45 minutes at 70°F (21°C). Cures completely in 24 hours. Do not recoat in less than 48 hours, or lifting may occur. Can should be at room temperature (approximately 70°F/21°C) before spraying for best results. **DO NOT USE ON ELECTRICAL EQUIPMENT OR MACHINERY WHILE IN OPERATION.**

**DANGER!** Keep away from heat, spark, or open flame. Avoid prolonged overexposure to sunlight, which may cause bursting. Do not puncture, incinerate or store above 120°F (49°C). May cause flash fire. Avoid continuous breathing of vapors and mist. Use with adequate ventilation. If you experience eye watering, headaches, nausea or dizziness, increase fresh airflow and/or wear respiratory protection. **HARMFUL OR FATAL IF SWALLOWED. FIRST AID:** If swallowed, do not induce vomiting. Call physician immediately. If eye contact occurs, flush eyes with plenty of water for 15 minutes. For skin contact, wash thoroughly with soap and water. In either case, if irritation persists, see physician immediately. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

**HAZARDOUS CONTENTS:** n-Butyl Acetate 123-86-4, Methyl Ethyl Ketone 78-93-3, Dimethyl Ether Propellant 115-10-6.

SHAKE WELL BEFORE USE



**DANGER!** Extremely flammable gas. Extremely flammable aerosol. Pressurized container; may burst if heated. Highly flammable liquid and vapor. Flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.



**KEEP AWAY FROM CHILDREN**

For Safety Data Sheets go to [www.aervoe.com](http://www.aervoe.com).

**AERVOE INDUSTRIES INC.**  
 Gardnerville, NV 89410 • 800-227-0196



106084; SW CS: -4/12/18