

AERVOE INDUSTRIES

ToolMates

# FOOD GRADE LUBE OIL 932

Huile de Lubrification de Qualité Alimentaire  
Aceite Lubricante de Calidad Alimenticia

NSF

Nonfood Compounds  
Category Code H1  
Registration #137954

- NSF H-1 Registered
- Ejector Pin Lube
- Excellent Silicone Spray Substitute
- Dielectric up to 30 kV

The Professional's Choice

**DANGER !**  
EXTRÊMEMENT INFLAMMABLE !  
CONTENU SOUS PRESSION.  
VAPEURS NOCIVES, NOCIF OU  
FATAL EN CAS D'INGESTION.  
(Lire les précautions au verso)

**DANGER!**  
EXTREMELY FLAMMABLE!  
CONTENTS UNDER PRESSURE.  
VAPORS HARMFUL, HARMFUL  
OR FATAL IF SWALLOWED.  
(Read cautions on back panel)

**¡PELIGRO!**  
¡EXTREMADAMENTE  
INFLAMABLE! CONTENIDO BAJO  
PRESIÓN. VAPORES PERJUDICIALES.  
PERJUDICIAL O FATAL SI TRAGADO.  
(Lea cuidados en atrás panel)

Net wt. 11 oz. (312 g)

SHAKE WELL BEFORE USE

## #932 FOOD GRADE LUBE OIL

**DESCRIPTION:** An economical, odorless general-purpose lubricating oil. NSF H-1 registered FDA 21 CFR 178.3570 for use in federally inspected facilities. Excellent cohesive and adhesive properties. Does not contain silicone. Penetrates and loosens rust and other corrosion. Provides lubrication and rust prevention with the ability to separate from water even under acid/alkali conditions.

**DIRECTIONS:** Align sprayhead with black mark on valve rim. Apply to clean surface 8-10 inches away. Use extension tube for pinpoint accuracy. Test on plastic before use.

**DO NOT USE ON ELECTRICAL EQUIPMENT OR MACHINERY WHILE IN OPERATION.**

**DANGER!** Never use or store near sparks, heat, open flame or sources of ignition. Do not puncture, incinerate or store container above 120°F (49°C). May cause flash fire.

**VAPOR HARMFUL.** Avoid continuous breathing of vapors and mist. Use with adequate ventilation. If you experience eye watering, headaches, nausea or dizziness, increase fresh airflow and/or wear NIOSH approved respiratory protection.

**AVOID CONTACT WITH SKIN AND EYES.**

**FIRST AID:** If swallowed, do not induce vomiting. Call physician immediately. If eye contact occurs, flush eyes with plenty of water for 15 minutes. For skin contact, wash thoroughly with soap and water. In either case, if irritation persists, see physician immediately.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**HAZARDOUS CONTENTS:** Aliphatic Hydrocarbon 64742-47-8, White Mineral Oil 8042-47-5, Hydrocarbon Propellant 68476-86-8.

**VOC Category: Multipurpose Lubricant | <25% VOC, <0.45 MIR**



**DANGER:** Extremely flammable gas. Extremely flammable aerosol. Pressurized container, may burst if heated. May be fatal if swallowed and enters airways.

**DANGER:** Gaz extrêmement inflammable. Aérosol extrêmement inflammable. Récipient pressurisé; peut éclater si chauffé. Peut être mortel en cas d'ingestion et de pénétration dans les voies respiratoires.

**¡PELIGRO!** Gas extremadamente inflamable. Aerosol sumamente inflamable. Recipiente a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y penetración en las vías respiratorias.



**KEEP AWAY FROM CHILDREN**  
For Safety Data Sheets go to [www.aervoe.com](http://www.aervoe.com).  
**AERVOE INDUSTRIES INC.**  
Gardenville, NV 89410 • 800-227-0196



1.6932; SW CS; 2/20/20