



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

## 1.) Identification of the Mixture and of the Company

Product identifier: **Carton Adhesive - Aerosol**

Product name:  
**8190 Hi-Strength Adhesive**

Relevant identified uses of the substance: Adheres to almost any surface or material - wood, paper, glass, plastic, cardboard and leather.

Uses advised against: Poorly ventilated area.

|                             |   |
|-----------------------------|---|
| CAS No:                     | <b>Not Applicable (mixture)</b>           |
| EC No:                      | <b>Not Applicable (mixture)</b>           |
| Index No:                   | <b>Not Applicable (mixture)</b>           |
| Manufacturer/Supplier:      | <b>Aervoe Industries Incorporated</b>     |
| Street address/P.O. Box:    | <b>1100 Mark Circle</b>                   |
| Country ID/Postcode/Place:  | <b>Gardnerville, Nevada 89410</b>         |
| Telephone number:           | <b>1-775-782-0100</b>                     |
| e-mail:                     | <b>mailbox@aervoe.com</b>                 |
| National contact:           | <b>Aervoe Industries Incorporated</b>     |
| For Product Information:    | <b>1-800-227-0196</b>                     |
| Emergency telephone number: | <b>1-800-424-9300 (CHEMTREC – 24 hrs)</b> |

## 2. Hazards identification

### Classifications

Physical Hazards:           Aerosol - Category 1  
                                      Flam. Liq. 2

Health Hazards:            Repr. 2  
                                      Asp. Tox. 1  
                                      STOT RE 2  
                                      Skin Irrit. 2  
                                      STOT SE 3  
                                      Eye Irrit. 2

Environmental Hazards:    Aquatic Chronic 2

### Labeling

Signal Word:                Danger

Hazard Statements:        H220 – Extremely flammable gas.  
                                  H222 – Extremely Flammable Aerosol  
                                  H225 – Highly flammable liquid and vapour  
                                  H229 – Pressurized container: may burst if heated  
                                  H304 – May be fatal if swallowed and enters airways



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

- H315 – Causes skin irritation
- H319 – Causes serious eye irritation
- H335 – May cause respiratory irritation
- H336 – May cause drowsiness or dizziness.
- H361 – Suspected of damaging fertility or the unborn child .
- H373 – May cause damage to nervous system through prolonged or repeated exposure(Inhalation)
- H411 – Toxic to aquatic life with long lasting effects.

- Precautionary Statements:
- P101 - If medical advice is needed, have product container or label at hand
  - P102 - Keep out of reach of children
  - P103 - Read label before use
  - P210 - Keep away from heat/sparks/open flames/hot surfaces - no smoking
  - P211 - Do not spray on an open flame or other ignition source
  - P251 - Pressurized container: Do not pierce or burn, even after use
  - P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
  - P262 - Do not get in eyes, on skin, or on clothing
  - P264 - Wash ... thoroughly after handling
  - P280 - Wear protective gloves/eye protection/face protection
  
  - P303+P361+P353 - If on skin or hair, remove/takeoff immediately all contaminated clothing. Rinse skin with water/shower.
  - P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
  - P501 - Dispose of contents/container in accordance with local/regional/national/international regulation
  - P251 - Pressurized container: Do not pierce or burn, even after use



Symbols/Pictograms:

### 3. Composition / Information on Ingredients

#### Composition

| Chemical               | Synonyms         | CAS Number | EINECS Number | Weight Percent | Hazard Category                           | H-Code               |
|------------------------|------------------|------------|---------------|----------------|---|----------------------|
| Methyl Acetate         | Methyl Ethanoate | 79-20-9    | 201-185-2     | 15-40%         | Flam. Liq. 2<br>Eye Irrit. 2<br>STOT SE 3 | H225<br>H319<br>H336 |
| Hydrocarbon Propellant | LPG              | 68476-86-8 | 270-705-8     | 15-40%         | Press. Gas<br>Flam. Gas 1                 | H220<br>H229         |
| Hexane                 | n-Hexane         | 110-54-3   | 203-777-6     | 10-30%         | Flam. Liq. 2<br>Repr. 2                   | H225<br>H361f *      |



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

|                             |  |         |           |          |  |   |
|-----------------------------|--|---------|-----------|----------|--|---|
|                             |  |         |           |          | Asp. Tox. 1<br>STOT RE 2 *<br>Skin Irrit. 2<br>STOT SE 3<br>Aquatic<br>Chronic 2 | H304<br>H373 **<br>(nervous system)<br>(inhalation)<br>H315<br>H336<br>H411 |
| Para-Chlorobenzotrifluoride | 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | 98-56-6 | 202-681-1 | 5-10%    | Flam liq 3<br>skin irrit 2<br>eye irrit 2<br>STOT SE 3                           | H226<br>H315<br>H319<br>H335  |
| Acetone                     | Propanone  | 67-64-1 | 200-662-2 | 0.5-1.5% | Flam. Liq. 2<br>Eye Irrit. 2<br>STOT SE 3  | H225, H319,<br>H336   |

## Other Product Information

Chemical Identity: Mixture

## 4.) First Aid Measures

**General Advice:**

If symptoms persist, always call a doctor.

**Inhalation First Aid:**

Remove victim to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention immediately.

**Skin Contact First Aid:**

Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse.

**Eye Contact First Aid:**

If contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention immediately.

**Ingestion First Aid:**

If swallowed, wash out mouth with water provided the person is conscious. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Most Important**

**Symptoms/Effects:**

Exposure may cause slight irritation to the skin, eyes, and respiratory tract. Excessive exposure may cause central nervous system effects.

## 5. Fire Fighting Measures

Flammable Properties:

Aerosol

Auto Ignition Temperature:

Not Available

Suitable extinguishing media:

Carbon dioxide, dry chemical, water spray.



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

Unsuitable extinguishing media: None known  
Special hazards arising from the substance or mixture: None known  
Hazardous combustion products: Carbon dioxide, Carbon monoxide  
Fire & Explosion Hazards: Closed Containers may rupture due to the buildup of pressure from extreme temperatures.  
Precautions for fire-fighters: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. In the event of a fire, wear full protective clothing and NIOSH- approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

## 6. Accidental Release Measures

### PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

### SPILL CLEAN-UP PROCEDURES:

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.
- 5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

## 7. Handling and Storage

### Handling:

Flammable Aerosol, use in a well ventilated area.  
Do not use near sources of ignition.  
Do not to eat, drink and smoke while working with this material.  
Wash hands after use.

### Conditions for safe storage, including any incompatibilities:

Store out of direct sunlight.  
Storage Temperature: 32° to 120°F (0° to 49°C).  
No known incompatibilities.

## 8. Exposure Controls / Personal Protection

### Appropriate engineering controls:

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.  
Keep away from sources of ignition.  
Take precautionary measures against static discharge.

### Personal Protection:



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

## Skin protection

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

## Respiratory protection:

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

| Hazardous Ingredient                               | CAS Number | ACGIH TLV (TWA) | ACGIH TLV (STEL) | OSHA PEL (TWA) | OSHA PEL (STEL) |
|--|------------|-----------------|------------------|----------------|-----------------|
| Methyl Ethanoate                                   | 79-20-9    | 200ppm          | 250ppm           | 200ppm         | N/AV            |
| LPG  | 68476-86-8 | N/AV            | N/AV             | N/AV           | N/AV            |
| n-Hexane   | 110-54-3   | 50ppm           | N/AV             | 500ppm         | N/AV            |
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | 98-56-6    | N/AV            | N/AV             | N/AV           | N/AV            |
| Propanone  | 67-64-1    | 500ppm          | 750ppm           | 1000ppm        | N/AV            |

\*Values are based on the 2014 Guide to Occupational Exposure Values by ACGIH

## 9. Information on Basic Physical and Chemical Properties

|  |   |
|--|---|
| Appearance: Amber, clear                         | Odor: Hydrocarbon Odor                        |
| Odor Threshold: N/AV                             | pH: Not Applicable (solvent Base)             |
| Melting Point: N/AV                              | Freezing Point: N/AV                          |
| Initial Boiling Point: N/AV                      | Boiling Point Range: N/AV                     |
| Flash Point: <0° F (-18° C)                      | Evaporation Rate: Faster than n-Butyl Acetate |
| Flammability Solid/Gas: Flammable gas            | LEL: N/AV UEL: N/AV                           |
| Vapor Pressure: N/AV                             | Vapor Density: Heavier Than Air               |
| Relative Density: N/AV                           | Solubility: Negligible                        |
| Partition Coefficient:<br>n-octanol/ water: N/AV | Auto-ignition Temperature: N/AV               |
| Decomposition Temperature: N/AV                  | Viscosity: N/AV                               |
| Explosive Properties: N/AV                       | Oxidizing Properties: N/AV                    |

## 10. Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions

Chemical stability: Stable under normal conditions

Conditions to avoid: Heat and ignition sources

Incompatible materials: Strong Oxidizing Agents

Hazardous decomposition products: Will not occur



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

## 11. Toxicological Information

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data: (n-Hexane) LD50: 2870mg/kg (Rat - Oral)  
(Acetone) 5800 mg/kg (Rat-Oral)  
(Acetone) 21000 ppm/8 hr (Rat-Inha)

Eye irritation data: N/AV

Skin irritation/sensitization/absorption data: N/AV

Reproductive toxicity data: N/AV

Mutagenicity data: Muta. 1B

Symptoms associated with physical contact: N/AV

Acute/chronic effects from short/long term exposure: Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.

Known reportable carcinogens via the following agencies:

NTP: N/AV  
IARC: N/AV  
OSHA: TLV-A4

\* Petroleum distillates may contain chemical carcinogens in limited quantities (< 0.01%). These quantities are determined by the supplier/fraction/purity of the distillate during the manufacturing process. Chemicals that may be present within distillates are listed on California's prop 65 list such as ETHYLBENZENE, BENZENE, and TOLUENE.

## 12. Ecological Information

Ecotoxicity: **No Data Available**  
Persistence and degradability: **No Data Available**  
Bioaccumulative potential: **No Data Available**  
Mobility in soil: **No Data Available**  
Results of PBT and vPvB assessment: **No Data Available**  
Other adverse effects: **No Data Available**

## 13. Disposal Considerations



# Safety Data Sheet (SDS)

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

**Waste Disposal:** Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

**Product / Packaging disposal:** Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.

## 14. Transportation Information

### US DOT

| UN Number | Proper Shipping Name | Hazard Class | Packing Group  | Marine Pollutant | Special Provisions       |
|-----------|----------------------|--------------|----------------|------------------|--------------------------|
| UN1950    | Aerosols             | 2.1          | Not Applicable | Not Applicable   | Reference 49 CFR 172.101 |

### IMDG

| UN Number | Proper Shipping Name | Hazard Class | Packing Group  | Marine Pollutant | Special Provisions         |
|-----------|----------------------|--------------|----------------|------------------|----------------------------|
| UN1950    | Aerosols             | 2.1          | Not Applicable | Not Applicable   | Reference IMDG code part 3 |

### IATA:

| UN Number | Proper Shipping Name | Hazard Class | Packing Group  | Marine Pollutant | Special Provisions                        |
|-----------|----------------------|--------------|----------------|------------------|---|
| UN1950    | Aerosols, Flammable  | 2.1          | Not Applicable | Not Applicable   | Reference IATA Dangerous Goods Regulation |

## 15. Regulatory Information

### Workplace classification:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

### SARA Title 3:

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

**TSCA status:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**WHMIS:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the (M)SDS contains all of the information required by the CPR.

**PROP 65 (CA):** WARNING: Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



# Safety Data Sheet (SDS)

---

Date Prepared/Revised: 11/1/18 Version no.: 04 Supersedes: (1/31/2018)

## **16. Other Information**

This SDS has been completed in accordance with GHS Rev04 (2011): U.S OSHA, CMA, ANSI, Canadian WHMIS standards, and European Directives.

Date of Preparation/Revision: 1/31/2018

Supersedes: 1/31/2018

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.