



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

1.) Identification of the Mixture and of the Company

Product identifier: **RUST PROOF PAINT - WATER BASED**

Product name:

3000 Safety Purple 3010 Safety Red 3020 Safety Yellow 3030 Safety Blue 3040 Safety Green	3050 Safety Orange 3060 Safety Black 3070 Safety White 3120 Flat Black 3130 Flat White	3150 Agri. Red 3160 Agri. Green 3170 Agri. Blue 3490 Meter Gray (ANSI-49)
--	--	--

Relevant identified uses of the substance: Ideal for equipment maintenance in food plants, restaurants, schools and hospitals as well as O.E.M. production.

Uses advised against: Poorly ventilated areas

CAS No:	Not Applicable (mixture)
EC No:	Not Applicable (mixture)
Index No:	Not Applicable (mixture)
Manufacturer/Supplier:	Aervoe Industries Incorporated
Street address/P.O. Box:	1100 Mark Circle
Country ID/Postcode/Place:	Gardnerville, Nevada 89410
Telephone number:	001 (0) 1-775-782-0100
e-mail:	mailbox@aervoe.com
National contact:	Aervoe Industries Incorporated
For Product Information:	001 (0) 1-800-227-0196
Emergency telephone number:	001 (0) 1-800-424-9300 (CHEMTREC – 24 hrs) English Language Service

2. Hazards identification

Classifications

Physical Hazards: Aerosol - Category 2
 Flam. Gas 1
 Flam. Liq. 3
 Pres. Gas

Health Hazards: Eye Irrit. 2
 STOT SE 3

Environmental Hazards: N/AV

Labeling

Signal Word: Warning



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

Hazard Statements: H220 – Extremely flammable gas
 H223 – Flammable aerosol
 H226 – Flammable liquid and vapour.
 H229 – Pressurized container: may burst if heated
 H319 – Causes serious eye irritation.
 H335 – May cause respiratory irritation.
 H336 – May cause drowsiness or dizziness.

Precautionary Statements: P101 - If medical advice is needed, have product container or label at hand
 P102 - Keep out of reach of children
 P103 - Read label before use
 P210 - Keep away from heat/sparks/open flames/hot surfaces - no smoking
 P211 - Do not spray on an open flame or other ignition source
 P251 - Pressurized container: Do not pierce or burn, even after use
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
 P262 - Do not get in eyes, on skin, or on clothing
 P264 - Wash ... thoroughly after handling
 P280 - Wear protective gloves/eye protection/face protection

P303+P361+P353 - If on skin or hair, remove/takeoff immediately all contaminated clothing. Rinse skin with water/shower.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulation
 P251 - Pressurized container: Do not pierce or burn, even after use
 P273 – Avoid release to the environment.

Symbols/Pictograms:



3. Composition / Information on Ingredients

Composition

Chemical	Synonyms	CAS Number	EINECS Number	Weight Percent	Hazard Category	H-Code
Propylene Glycol	Propylene Glycol n-	1569-01-3	216-372-4	3-7%	N/AV	N/AV



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

Monopropyl Ether	Propyl Ether					
Butan-2-ol	2-Butanol	78-92-2	201-158-5	3-7%	Flam. Liq. 3 Eye Irrit. 2 STOT SE 3 STOT SE 3	H226 H319 H335 H336
Dimethyl Ether	DME	115-10-6	204-065-8	30-60%	Flam. Gas 1 Press. Gas	H220

Other Product Information

Chemical Identity: Mixture

4.) First Aid Measures

General Advice:	If symptoms persist, always call a doctor.
Inhalation First Aid:	Remove victim to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention immediately.
Skin Contact First Aid:	Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse.
Eye Contact First Aid:	If contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention immediately.
Ingestion First Aid:	If swallowed, wash out mouth with water provided the person is conscious. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Most Important Symptoms/Effects:	Exposure may cause slight irritation to the skin, eyes, and respiratory tract. Excessive exposure may cause central nervous system effects.

5. Fire Fighting Measures

Flammable Properties:	Aerosol
Auto Ignition Temperature:	Not Available
Suitable extinguishing media:	Carbon dioxide, dry chemical, water spray.
Unsuitable extinguishing media:	None known
Special hazards arising from the substance or mixture:	None known
Hazardous combustion products:	Carbon dioxide, Carbon monoxide
Fire & Explosion Hazards:	Closed Containers may rupture due to the buildup of pressure from extreme temperatures.



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

Precautions for fire-fighters: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. In the event of a fire, wear full protective clothing and NIOSH- approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

SPILL CLEAN-UP PROCEDURES:

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.
- 5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

7. Handling and Storage

Handling:

Flammable Aerosol, use in a well ventilated area.
Do not use near sources of ignition.
Do not to eat, drink and smoke while working with this material.
Wash hands after use.

Conditions for safe storage, including any incompatibilities:

Store out of direct sunlight.
Storage Temperature: 32° to 120°F (0° to 49°C).
No known incompatibilities.

8. Exposure Controls / Personal Protection

Appropriate engineering controls:

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.
Keep away from sources of ignition.
Take precautionary measures against static discharge.

Personal Protection:

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

Skin protection

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

Respiratory protection:

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Hazardous Ingredient	CAS Number	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)
Dimethyl Ether	115-10-6	20ppm	N/AV	N/AV	N/AV
Propylene Glycol Monopropyl Ether	1569-01-3	N/AV	N/AV	N/AV	N/AV
Butan-2-ol	78-92-2	100ppm	N/AV	N/AV	N/AV

*Values are based on the 2014 Guide to Occupational Exposure Values by ACGIH

9. Information on Basic Physical and Chemical Properties

Appearance: Color varies by product	Odor: Alcohol odor
Odor Threshold: N/AV	pH: Not Applicable (solvent Base)
Melting Point: N/AV	Freezing Point: N/AV
Initial Boiling Point: N/AV	Boiling Point Range: N/AV
Flash Point: <0° F (-18° C)	Evaporation Rate: Slower than n-Butyl Acetate
Flammability Solid/Gas: Flammable gas	LEL: 1.1% UEL: 18%
Vapor Pressure: N/AV	Vapor Density: Heavier Than Air
Relative Density: N/AV	Solubility: Negligible
Partition Coefficient: N/AV n-octanol/ water: N/AV	Auto-ignition Temperature: N/AV
Decomposition Temperature: N/AV	Viscosity: N/AV
Explosive Properties: N/AV	Oxidizing Properties: N/AV

10. Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions

Chemical stability: Stable under normal conditions

Conditions to avoid: Heat and ignition sources

Incompatible materials: Strong Oxidizing Agents

Hazardous decomposition products: Will not occur

11. Toxicological Information

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data: (Butan-2-ol) Acute oral LD50: 4900 mg / kg (rat)
(Butan-2-ol) LC50: 8500 ppm/4hr(Rat)
(Dimethyl Ether) LC50:164,000 ppm / 4 hr(Rat)

Eye irritation data: N/AV

Skin irritation/sensitization/absorption data: N/AV

Reproductive toxicity data: N/AV

Mutagenicity data: N/AV

Symptoms associated with physical contact: N/AV

Acute/chronic effects from short/long term exposure: Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.

Known reportable carcinogens via the following agencies:

NTP: N/AV

IARC: N/AV

OSHA: N/AV

* Petroleum distillates may contain chemical carcinogens in limited quantities (< 0.01%). These quantities are determined by the supplier/fraction/purity of the distillate during the manufacturing process. Chemicals that may be present within distillates are listed on California's prop 65 list such as ETHYLBENZENE, BENZENE, and TOLUENE.

12. Ecological Information

Ecotoxicity: **No Data Available**

Persistence and degradability: **No Data Available**

Bioaccumulative potential: **No Data Available**

Mobility in soil: **No Data Available**

Results of PBT and vPvB assessment: **No Data Available**

Other adverse effects: **No Data Available**



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

13. Disposal Considerations

Waste Disposal: Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

Product / Packaging disposal: Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.

14. Transportation Information

US DOT

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions
UN1950	Aerosols	2.1	Not Applicable	Not Applicable	Reference 49 CFR 172.101

IMDG

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions
UN1950	Aerosols	2.1	Not Applicable	Not Applicable	Reference IMDG code part 3

IATA:

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions
UN1950	Aerosols, Flammable	2.1	Not Applicable	Not Applicable	Reference IATA Dangerous Goods Regulation

15. Regulatory Information

Workplace classification:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

SARA Title 3:

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

TSCA status: All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.



Safety Data Sheet (SDS)

Date Prepared/Revised: 1/26/2015 Version no.: 01 Supersedes: (-)

WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the (M)SDS contains all of the information required by the CPR.

PROP 65 (CA): WARNING: This product may contain chemicals know to the state of California to cause cancer, birth defects or other reproductive harm.

16. Other Information

This SDS has been completed in accordance with GHS Rev04 (2011): U.S OSHA, CMA, ANSI, Canadian WHMIS standards, and European Directives.

Date of Preparation/Revision: 1/26/2015

Supersedes: (-)

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.