

Product Data Sheet

No. 11601 - 04/20

ROOF ACCESSORY & TRIM PAINT

AEROSOL CARB MIR: Flat ≤ 0.80

PRODUCT NUMBERS:

1601 - CEDAR	1607 - SMOKE	1613 - TERRA COTTA
1603 - RUSTIC BROWN	1608 - SLATE GRAY	1616 - ADOBE
1604 - DRIFTWOOD	1609 - RUSTIC BLACK	1625 - BONE WHITE
1606 - BIRCHWOOD	1612 - DARK BROWN	1626 - SIERRA TAN

I. GENERAL DESCRIPTION

Features: This high quality lacquer coating is formulated for exterior use on roofing accessories. This product is available in 12 of the most commonly used OEM colors. Durable color fastness, good hide and coverage. This product provides long term protection against rust, corrosion, and discoloration on metal and other roofing accessory materials. Easy application, great color selection, superior durability, while extending the life of all roofing accessory materials.

Benefits: Aervoe Roof Accessory & Trim Paint is a fast-drying industrial grade lacquer. Excellent adhesion to all metal, plastic, vinyl, wood and masonry surfaces. Provides a professional coating on surfaces where brush application may be difficult. The finish dries to the touch in minutes and yields a full cure in 24 hours. Exceptional resistance to water, sun (UV rays), snow, and other harsh environmental conditions.

Applications: Use on metal, plastic, vinyl, wood, concrete, and masonry. Specifically designed for roof vents, flashing, valleys, and other metal and/or plastic roof accessories.

Directions: For maximum adhesion, surface must be clean, dry and free of grease, rust, scale or any other loose particles. Over galvanized steel a primer is not recommended. Product should be used at temperatures between 60° and 85° (16° and 29°C) for best results. Shake can well for at least one minute after agitator ball begins to rattle. Shake can intermittently during use. Hold can 8 to 10 inches from surface and press spray head firmly. Apply with steady, even strokes; two light coats are better than one heavy coat. Clear spray tip after each use by turning can upside down and spraying for 2 seconds.

Limitations: Please refer to the Safety Data Sheets for specific information on material hazards, etc. Please check all plastic surfaces for adhesion and compatibility before each use.

Packaging:

Aerosol:	Cans (16 oz.)	12 oz. net wt. (340 g)	14.6 fl. oz. (432 ml)
	Case (12/case):	14 lbs. (6.35 kg)	0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES (Average for all colors)

Specifications:

Complies with CARB Flat and Non-flat MIR regulations for aerosol coatings.

Appearance:

Gloss at 60° Flat <5
Class Flat

Coverage:

Theoretical—at 1 mil dry 16 sq. ft./can.

Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch 5 min.
To handle 15 min.
Full cure 24 hrs.
To recoat Any time

Performance and Chemical Properties:

Weight per gallon 6.6 lbs.
Specific gravity 0.79
Flammability: Label marking Extremely flammable
Flash point <0°F (-18°C)
Operating temperature range 55° to 95°F (13° to 35°C)
Percent solids by weight 19%
Percent solids by volume 9 %
Percent pigment by volume 3 %
CARB MIR Flat <0.80
Exterior durability Excellent
Temperature resistance 300°F (149°C)
Color fastness Excellent
Adhesion Excellent over properly prepared surface
Mineral spirits resistance Excellent
Gasoline resistance Poor
Motor oil resistance Excellent
Pencil hardness HB

Base Materials:

Resin system Acrylic
Solvents (top two) Acetone, Methyl Acetate
Propellant system Hydrocarbon

III. SHIPPING, STORAGE AND HEALTH

UN number UN1950
Proper Shipping Description Aerosols
Hazard Class 2.1
Packing Group N/A
Limited Quantity Yes
Warehouse storage level number NFPA 30B Level 2
Storage temperature 32° to 120°F (0° to 49°C)
Shelf life 1 to 2 years
HMIS ratings
Health 2
Fire 4
Reactivity 1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.