

# Product Data Sheet

No. **26075** - 05/13

## DRY FILM LUBRICANT

### AEROSOL

PRODUCT NUMBERS: 6075

#### I. GENERAL DESCRIPTION

**Description:** A non-staining product that forms a slippery layer of translucent particles on rubber, wood, metals, nylon, epoxies, polypropylene, acrylics, and phenolic resins. Dry Film Lubricant is a dispersion of white, waxy particles of PTFE.

**Benefits:** This film has unique dry lubricating qualities. Excellent for temperatures up to 500° F for extended periods. This product reduces clean-up labor time and will not interfere with post-finishing operations.

**Application:** This product is ideal for extreme dust conditions, such as encountered in mining and quarry operations. Use on conveyors, chutes, precision and electrical equipment.

**Directions:** Shake can well. Hold 8 to 10 inches from surface and apply uniformly. For best results, can should be at room temperature 70° F (21° C). Do not use on electrical equipment or machinery while in operation.

**Limitations:** Please refer to the Safety Data Sheet for specific information on material hazards, etc. For industrial use in manufacturing facilities.

#### Packaging:

Cans - (211 x 604)	11 oz. net wt.. (312 grams)	14.6 fl. oz. (446 ml)
Case - 12 cans/case	13 lbs. (5.9 kg)	0.55 CF (0.016 CM)



**AerVOE Industries, Inc.**  
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service  
[www.aerVOE.com](http://www.aerVOE.com) • [mailbox@aerVOE.com](mailto:mailbox@aerVOE.com)

---

## II. CHARACTERISTICS & PROPERTIES

---

**Specifications:**

None

**Appearance:**

Non-foaming liquid

**Color:**

Light milky

**Odor:**

Ketone

**Dry Schedule:**

Not Applicable

**Performance and Chemical Properties:**

Weight per gallon .....	5.8 lbs
Specific gravity .....	0.70
Viscosity .....	N/A
Flammability: Label marking .....	Extremely Flammable
Flash point .....	<0° F (-18° C)
Operating temperature range .....	40° F to 110° F (5° to 43° C)
Active ingrediants by weight .....	2%
Volatile Organic Compound Level .....	72%
EPA VOC% Limit .....	Not Regulated
CARB VOC% Limit.....	I&I Exempt
Dielectric strength .....	TBD
Lubricity (FALEX FLC Test) .....	200 ft. lbs.
Penetrating ability .....	Excellent
Corrosion protection .....	Good

**Base Materials:**

.....PTFE, Acetone

**Propellent:**

.....Hydrocarbon

---

## III. SHIPPING, STORAGE AND HEALTH

---

UN number .....	UN1950
Proper Shipping Description .....	Aerosols
Hazard Class.....	2.1
Packing Group .....	N/A
Limited Quantity .....	Yes
Warehouse storage level number .....	NFPA 30B Level 2
Storage temperature .....	32° to 120°F (0° to 49°C)
Shelf life .....	1 to 5 years
HMIS ratings	
Health .....	2
Fire .....	4
Reactivity.....	1

---

## IV. MISCELLANEOUS

---

Contains no Ozone Depleting Substances (O.D.S.)

---

## V. WARRANTY

---

1-year performance warranty on all products from date of purchase. Report to home office or local Aervoe representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.

No. 26075 - 05/13