

# Product Data Sheet

No. **27038** - 05/23

## RED GREASE

CARB VOC <25%, MIR <0.45 (MULTI-PURPOSE LUBRICANT)

PRODUCT NUMBERS: 7038

### I. GENERAL DESCRIPTION

**Description:** Red Grease is a completely versatile product which combines the best qualities of many lubricants into one grease. It's unique formula is heavy duty and all-weather with a NLGI Grade 2 rating, in an aerosol package. The aluminum-complex based grease penetrates and forms a protective film to withstand all loads and speed. The red color provides easy visual inspection.

**Benefits:** Eliminates squeaks and squeals and provides excellent corrosion protection. Will not run or wash away. Provides excellent all-weather lubrication for moving parts including high pressure applications. Effective both indoors and outdoors in temperatures from 0° to 450°F (-17° to 232°C). Packaged in a convenient aerosol instead of a messy cartridge.

**Application:** Use on gears, ball and roller bearings, speed reducers, cams, pumps, bolts, studs, auto door hinges, cranking mechanisms.

**Directions:** Shake can well before use. For best results use at room temperature (70°F/21°C). Hold 2 to 4 inches away from part. For pinpoint accuracy or hard to reach areas, insert the extension tube into the sprayhead. Clear sprayhead by inverting can and spraying for 2 seconds after each use. If clogging occurs, remove tip and soak in a mild solvent. Protect other areas from over spray if necessary. **DO NOT USE ON ELECTRICAL EQUIPMENT OR MACHINERY WHILE IN OPERATION.**

**Limitations:** Please refer to the Safety Data Sheet for specific information on material hazards, etc.

**Packaging:**

Aerosol:

Cans (16 oz.)  
12 cans/case

11 oz. net wt. (312 g)  
13 lbs. (5.9 kg)

15.7 fl. oz. (371 mL)  
0.47 CF (0.013 CM)



**Aervoe Industries, Inc.**  
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service  
[www.aervoe.com](http://www.aervoe.com) • [mailbox@aervoe.com](mailto:mailbox@aervoe.com)

---

## II. CHARACTERISTICS & PROPERTIES

---

### Specifications:

NLGI Grade 2

### Appearance:

Red viscous grease

### Dry Schedule:

Not applicable

### Performance and Chemical Properties:

Weight per gallon ..... 6.33 lbs.  
Specific gravity ..... 0.77  
Viscosity in centipoise ..... Not applicable  
Flammability: Label marking ..... Extremely Flammable  
Flash point ..... <20° F (-7° C)  
Active ingredients by weight ..... 45%  
EPA VOC (multi-purpose lubricant) ..... Not Regulated  
CARB VOC (multi-purpose lubricant) ..... <25% VOC, <0.45 MIR  
Operating temperature range ..... 0° to 450°F (-17° to 232°C)  
Pour point ..... Not applicable  
Dielectric strength ..... TBD  
Lubricity (FALEX FLC Test) ..... >200 ft. lbs.  
Copper strip corrosion: 24 hrs @212°F-1A ..... Good

### Base Materials

Solvents ..... Grease, Petroleum Distillates  
Propellant system ..... Hydrocarbon

---

## III. SHIPPING, STORAGE AND HEALTH

---

UN number	<b>Aerosol</b> UN1950
Proper Shipping Description	Aerosols
Hazard Class	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 2
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 5 years
HMIS ratings	
Health	1
Fire	4
Reactivity	1

---

## IV. MISCELLANEOUS

---

Contains no Ozone Depleting Substances (O.D.S.)

---

## V. WARRANTY

---

1-year performance warranty on all products from date of purchase. Report to home office or local Aerove representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.