

Product Data Sheet

No. **33095** - 05/23

MOLD CLEANER

PRODUCT NUMBERS: 63095 - 10.5-OZ. NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: Excellent cleaning power that works fast to remove silicone, grease, oil and residue from molds. Evaporates quickly and leaves no residue. Designed for in-place cleaning of all metal molds during use or for superior clean up prior to storage.

Benefits: Remove moisture, dirt, oil, release agent residue and other contaminants quickly without remove the mold from the machine. It's non-abrasive and non-conductive. Does not contain trichloroethylene (TCE) or perchloroethylene (PERC) solvents that are not allowed in certain uses.

Applications: Use on all metal molds, pins, dies and tooling. Safe on most plastic but check compatibility before use.

Directions: Before using, cover any area not being cleaned. Hold can 12-14 inches from the surface to be sprayed. Saturate parts as needed and wipe clean, with lint free cloth to remove surface contamination. Store at room temperature. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Material Safety Data Sheet for specific information on material hazards, etc.

Packaging:

Aerosol:

Cans (211x604)
12 cans/case

10.5 oz. net wt. (298 grams)
13 lbs. (5.9 kg)

12.6 fl. oz. (372 ml)
0.47 CF (0.013 CM)



AerVOE Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aerVOE.com • mailbox@aerVOE.com

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Clear transparent liquid

Color:

Colorless

Odor:

Naphthalenic

Dry Schedule:

Not applicable

Performance and Chemical Properties:**Aerosol**

Weight per gallon	6.8 lbs./gallon
Specific gravity	0.8
Viscosity in centipoise	Not applicable
Flammability: Label marking	Extremely Flammable
Flash point.....	< 20°F
Active ingredients by weight	96%
CARB VOC limit (single use clenaer)	Exempt
EPA VOC limit	Not Regulated
Operating temperature range.....	40° to 110°F (4° to 43°C)
Boiling point @ 760mm Hg	NA
Evaporation rate (Butyl Acetate = 1)	1
KB value.....	64
Dielectric strength	NA
Surface tension	TBD
Food contact rating	Not applicable

Base Materials: Heptane, Parachlorobenzotrifluoride (PCBTF)**Propellant system:** Carbon Dioxide

III. SHIPPING, STORAGE AND HEALTH

Aerosol

U.N number.....	UN 1950
D.O.T. container spec.....	2Q
D.O.T. shipping description	Consumer Commodity
Warehouse storage level number	NFPA 30B Level 3
Hazardous class (CFR-49).....	2.1
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 3 years
HMIS ratings	
Health	2
Fire	3
Reactivity.....	0

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.