

Product Data Sheet

No. **36095** - 02/20

LAYOUT FLUID REMOVER

AEROSOL AND BULK LIQUID

PRODUCT NUMBERS: 6095 - 10.5 OZ. NET WT AEROSOL

Product number plus letter designation is as follows:
G = 2 one-gallon cans; F = 1 five-gallon pail; D = 50-gallon drum

I. GENERAL DESCRIPTION

Description: Layout Fluid Remover is fast acting and completely dissolves all layout fluids from dies and related equipment without leaving a residue.

Benefits: Non-chlorinated and fast-acting remover effectively dissolves ink without leaving a residue. The aerosol form delivers in a high-pressure spray to apply the product exactly where you wish to clean.

Application: Use to remove layout fluids and ink from molds and tools or from the surface of completed work.

Directions: For best results product should be used at temperatures between 60° and 80° F (16° and 27° C). A heavy coating is recommended. Wait a few seconds for solvent to dissolve the film and then wipe away with a rag or paper towel. **Aerosol:** Align spray head with black mark on valve rim to ensure complete evacuation. Hold can 2 to 6 inches from surface to be cleaned. **Bulk:** Apply with clean sprayer or rag. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Material Safety Data Sheet for specific information on material hazards, etc.

Packaging:

| | | | |
|----------|---------------------------|----------------------|----------------------|
| Aerosol: | Cans (211x604): | 10.5 net wt. (298 g) | 14.5fl. oz. (429 ml) |
| | Case (12/case): | 12 lbs. (5.6 kg) | 0.55 CF (0.015 CM) |
| Bulk: | Case (2 gallons/case): | 17 lbs. (7.7 kg) | 1.0 CF (0.028 CM) |
| | 5-gallon pail: | 36 lbs. (16.3 kg) | 1.2 CF (0.034 CM) |
| | 50-gallon drum (mt. rd.): | 362 lbs. (164.5 kg) | 8.5 CF (0.240 CM) |

II. CHARACTERISTICS & PROPERTIES

Specifications: Single use cleaner (exempt)

Appearance:

Non-foaming liquid

Color:

Colorless, transparent

Odor:

Ketone

Performance and Chemical Properties:

| | Aerosol | Bulk |
|--|----------------------------|----------------------------|
| Weight per gallon | 5.9 lbs | 6.3 lbs |
| Specific gravity | 0.71 | 0.76 |
| Viscosity in centipoise (@ 70°F / 21° C) | Not applicable | 2.0 cPs @ 60 rpm Sp#2 |
| Flammability: Label marking | Extremely Flammable | Extremely Flammable |
| Flash point..... | < 0 F (-18°C) | 15°F (-24°C) |
| Application temperature (air & substrate)..... | 30° to 110°F (-1° to 43°C) | 30° to 110°F (-1° to 43°C) |
| Active ingredients by weight..... | 80% | 100% |
| Volatile Organic Compound level..... | 57% | 742 g/L |

Base Materials:

| | | |
|--------------------------|---|---|
| Solvents (top two) | Acetone, Light Aliphatic Petroleum Naptha | Acetone, Light Aliphatic Petroleum Naptha |
| | | Acetone, Light Aliphatic Petroleum Naptha |
| Propellant..... | Hydrocarbon | Not applicable |

III. SHIPPING, STORAGE AND HEALTH

| | Aerosol | Bulk |
|--------------------------------------|--------------------------------|---|
| IMDG number..... | 1950..... | UN 1993 |
| D.O.T. container spec..... | 2Q..... | 1A1, 1A2, 3A1 |
| D.O.T. shipping description | Consumer Commodity..... | Flammable liquid N.O.S. (Light Aliphatic Petroleum Naptha, Acetone) |
| Warehouse storage level number | NFPA 30B Level 3..... | Flammable Liquid class 1B |
| Hazardous class (CFR-49)..... | Class 2.1..... | Flammable Liquid |
| Storage temperature | 32° to 120°F (0° to 49°C)..... | 32° to 120°F (0° to 49°C) |
| Shelf life | 1-3 years..... | 3-5 years |
| HMIS ratings | | |
| Health | 2..... | 2 |
| Fire..... | 4..... | 3 |
| Reactivity | 0..... | 0 |

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.