

# Product Data Sheet

No. **38079** - 08/19

## DRIVE BELT DRESSING

### AEROSOL AND BULK LIQUID

PRODUCT NUMBER: 8079 - 12 OZ. NET WT. AEROSOL

PRODUCT NUMBER PLUS LETTER DESIGNATION IS AS FOLLOWS:  
Q = 12 ONE-QUART CANS

#### I. GENERAL DESCRIPTION

**Description:** This product is specifically formulated to minimize belt slippage and increase grip, pulling power, and belt life.

**Benefits:** Maintain suppleness and flexibility of new or used belts. Reduces belt squeak and squealing due to traction loss. Increases motor efficiency and reduces premature belt wear. Cleans belts of accumulation of dirt and grease. Safe for use on rubber, leather, canvas, or any other composition or fabric. Can be used in wet outdoor conditions.

**Application:** Use on V-belts, round, toothed, flat, abrasive, sanding, appliance, business machines, water pumps, industrial drives, fans, etc.

**Directions:** For best results, product should be used at temperatures between 60° and 80°F (16° and 27°C). Apply sparingly until drive surface is completely covered. Occasional applications at regular intervals (depending on usage, tension, and belt load) will help maintain full power transmission. **Aerosol:** Align spray head with black mark on valve rim to ensure complete evacuation. Before spraying, shake can vigorously for 10 to 20 seconds after agitator ball is heard and intermittently thereafter. Hold can 8 to 10 inches from belt. Spray back and forth across drive surface. Do not spray excessively. **Bulk:** Apply with clean sprayer, brush, rag, or by dipping. Apply lightly and evenly. Do not use on electrical equipment or machinery while in operation.

**Limitations:** Please refer to the Safety Data Sheet for specific information on material hazards, etc.

#### Packaging:

Aerosol:	Cans (16 oz.)	12 oz. net wt. (340g)	16.7 fl. oz. (494ml)
	Case - 12 cans /case	13 lbs. (5.9kg)	0.47 CF (0.013 CM)
Bulk:	1 case of 12 quarts (mt. F.)	37 lbs. (16.78kg)	0.29 CF (0.008 CM)

---

## II. CHARACTERISTICS & PROPERTIES

---

**Specifications:**

None

**Appearance:**

Non-foaming liquid

**Color:**

Clear, transparent

**Odor:**

Hydrocarbon

**Coverage:**

	<b>Aerosol</b>	<b>Bulk</b>
Theoretical (at 1 mil dry) .....	29 sq. ft. ....	568 sq. ft./gallon
Practical (at 1/2 mil dry) .....	19 sq. ft. ....	1,136 sq. ft./gallon

**Drying Schedule (at 77° F [25° C], 50% Humidity at 1 mil dry):**

Remains tacky

**Performance and Chemical Properties:**

Weight per gallon .....	5.77 lbs. ....	6.36 lbs.
Specific gravity .....	0.69 .....	0.76
Viscosity (centipoise @ 70° F / 21° C) .....	Not Applicable .....	6.5 cPs @ 60 rpm Sp#2
Flammability: Label marking .....	Extremely flammable .....	Flammable
Flash point.....	<0°F (-18°C) .....	15°F (-5°C)
Application temperature range (air & substrate).....	40° to 110°F (5° to 43°C) .....	40° to 110°F (5° to 43°C)
Temperature resistance.....	>400°F (204°C) .....	400°F (204°C)
Active ingredients by weight .....	20% .....	25%
CARB VOC (not regulated).....	Not regulated .....	Not regulated
Food contact rating .....	USDA accepted Category P1 .....	USDA accepted Category P1

**Base Materials:**

Resin system.....	Polybutene Polymer .....	Polybutene Polymer
Solvents (top two) .....	Aliphatic Petroleum Distillates .....	Aliphatic Petroleum Distillates
Propellant.....	Hydrocarbon.....	Not Applicable

---

## III. SHIPPING, STORAGE AND HEALTH

---

	<b>Aerosol</b>	<b>Non Aerosol</b>
UN number.....	UN1950.....	UN1993
Proper Shipping Description .....	Aerosols.....	Flammable Liquid, n.o.s. (VM&P Naptha, Aliphatic Petroleum Distillates)
Hazard Class.....	2.1.....	3
Packing Group .....	N/A.....	II
Limited Quantity .....	Yes.....	Container Size Determines Applicability
Warehouse storage level number .....	NFPA 30B Level 3.....	N/A
Storage temperature .....	32° to 120°F (0° to 49°C).....	32° to 120°F (0° to 49°C)
Shelf life .....	1 to 2 years.....	3 to 5 years
HMIS ratings		
Health.....	1 .....	2
Fire .....	3 .....	3
Reactivity.....	1 .....	1

---

## IV. MISCELLANEOUS

---

Contains no Ozone Depleting Substances (O.D.S.)

---

## V. WARRANTY

---

1-year performance warranty on all products from date of purchase. Report to home office or local Aervoe representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.