

Product Data Sheet

No. **51218** - 09/15

MAX HIGH PERFORMANCE FUEL BLEND CARTRIDGE

AEROSOL VOC <100%

PRODUCT NUMBER: 1218 - 8.1 OZ. NET WT.



I. GENERAL DESCRIPTION

Features: Max High Performance Fuel Blend Cartridge contains an 80% isobutane and 20% propane mixture that provides a reliable and clean burning fuel for portable butane appliances utilizing a universal threaded valve.

Benefits: The 80/20 mixture provides a stable pressure and BTU output, which is ideal when operating at low temperature or high elevation.

Uses: Ideal fuel source for cooking and lighting while backpacking at high altitude or low temperature. May also be used as an emergency fuel source during an power outage.

Warnings: Extremely Flammable. DO NOT use or store near other sources of combustibles, heat or flame. DO NOT puncture or incinerate. Not for indoor use. Use in well ventilated area. DO NOT attempt to light appliance or use fuel when gas odor or leakage is detected. Once all of the fuel is used, discard empty can in accordance with local aerosol disposal regulations. Refer to the Safety Data Sheet for specific information on material hazards.

This product contains and when burned produces chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Packaging:

Each can:	8.1 oz. net wt. (230 g)	13.7 fl. oz. (405 ml)	
Case (12/case):	11.25 lbs. (5.1 kg)	0.6 CF (0.02 CM)	17.75" H x 13.5" W x 4.25" H



AerVOE Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aerVOE.com • mailbox@aerVOE.com

II. CHARACTERISTICS AND PROPERTIES

Specifications:

None

Appearance:

Clear Gas

Odor:

Odorized gas

Performance and Chemical Properties:

Weight per gallon	4.83
Specific gravity	0.58 @ -50°C
Flammability:	
Label marking	Extremely flammable
Flash point	< 0°C)
Volatile Organic Compound level	100%
Operating temperature range	40° to 110°F (5° to 43° C)
Boiling temperature range	-40° to 34°F (-40° to 1°C)
Auto ignition temperature range	761° to 842°F (405° to 450°C)
Vapor pressure	51 psi @ 70°F

Base Materials

.....LPG Hydrocarbon Propellant

III. SHIPPING, STORAGE AND HEALTH

UN number	UN1075
Proper Shipping Description	Petroleum Gasses, Liquefied
Hazard Class	2.1 Flammable Gas
Packing Group	N/A
Limited Quantity	No
Warehouse storage level number	NFPA 30B Level 3
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	> 2 years

HMIS ratings

Health	1
Fire	4
Reactivity	0

IV. MISCELLANEOUS

Does not contain ozone depleting substances.

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.